

VLR SAFETY TAILGATE TALK

May 2016

Subject: Aerial Lifts Protect Yourself

Date: _____

Location (garage, mm, etc...):

Instructions:

Safety Coordinators & Supervisors should use this Tailgate Talk as a guide for discussion during their safety meetings. The primary purpose of the safety meetings is to give crews the opportunity to discuss any safety related concerns they may have.


Once the meeting has concluded, the Presenter should have each employee sign this form and include their Employee ID# in the spaces below.

TGT Presenter: _____

Aerial lifts are vehicle-mounted, boom-supported aerial platforms, such as cherry pickers or bucket trucks, used to access utility lines and other aboveground job sites. The major causes of fatalities are falls, electrocutions, and collapses or tip overs. Employers must take measures to ensure the safe use of aerial lifts by their workers if they are required to use this equipment in the course of their employment.

Safe Work Practices:

- Make sure that workers who operate aerial lifts are properly trained in the safe use of the equipment.
- Maintain and operate elevating work platforms according to the manufacturer's instructions.
- Never override hydraulic, mechanical, or electrical safety devices.
- Never move the equipment with workers in an elevated platform unless this is permitted by the manufacturer.
- Do not allow workers to position themselves between overhead hazards, such as joists and beams, and the rails of the basket. Movement of the lift could crush the worker.
- Maintain a minimum clearance of at least 10 feet, or 3 meters, away from the nearest energized overhead lines.
- Always treat power lines, wires and other conductors as energized, even if they are down or appear to be insulated.
- Use a body harness or restraining belt with a lanyard attached to the boom or basket to prevent the worker(s) from being ejected or pulled from the basket.
- Set the brakes and use wheel chocks when on an incline.
- Use outriggers, if provided.
- Do not exceed the load limits of the equipment. Allow for the combined weight of the worker, tools and materials.



Name	Employee
1.	
2.	
3.	
4.	
5.	
6.	
7.	
8.	
9.	
10.	
11.	
12.	
13.	
14.	
15.	
16.	

*OSHA Quick Card

VTTC
SAFETY